



## HP Encastrables / CL-3T

|                     |                                     |
|---------------------|-------------------------------------|
| design              | Full Range                          |
| Woofer              | 8 inch                              |
| Impedance           | 8Ω / 100V / 70V                     |
| Power Handling RMS  | 20 Watts                            |
| Programme Watts     | 40 Watts                            |
| SPL 1W/1m (dB)      | 90 dB                               |
| Max @1m (dB)        | 106 dB                              |
| Frequency Responce  | 60 Hz-20 kHz                        |
| Dispersion          | 140° Conical                        |
| Crossover Frequency | 3 kHz                               |
| Ceiling Thickness   | 10 - 35 mm                          |
| Hole Cutout Ø       | Ø239 mm                             |
| Dimensions Ø x H    | Ø273 x 100 mm                       |
| Weight              | 1.4 kg                              |
| Connector           | Spring loaded terminal              |
| <b>Tappings</b>     |                                     |
| 100V                | 6W,<br>3W,<br>1.5W,<br>0.8W         |
| 70V                 | 3W,<br>1.5W,<br>0.75W,<br>0.4W      |
| IMP Ω               | 1.7K,<br>3.3K,<br>6.7K,<br>13K      |
| Colour              | White Ral9003                       |
| Speaker Cables      | Minimum Diameter 2.5mm <sup>2</sup> |

