



TRS Series / INFRA SUB

Design	Subwoofer, Reflex tuned push-pull configuration
Impedance	4 Ohm
Power Handling (AES)	2400 Watts (continuous)
Maximum Power Handling (AES)	4800 Watts (program) 9600 Watts (peak 10 ms)
Sensitivity 2.83V / 1m	101 dB
Maximum SPL	135 dB (cont. max SPL / 1m) 141 dB peak
Frequency Response -3 dB	24 Hz – 45 Hz
Dispersion	Omni
SYSTEM OPERATION	
Recommended Amplification	2400-4800 Watts
System Controller	Ohm DSP Solutions, HPF and LPF required
Speaker Cables	Min 2 x 4 mm ² , Preferred 2 x 6 mm ²
PRODUCT FEATURES	
Components	2 x 18" Low Frequency Drivers
Crossover	-
Connectors	2 x 4 pole Speakon Connectors
Dimensions (H x W x D)	576 mm x 1156 mm x 900 mm
Weight (kg)	96
Shipping Weight (kg)	00 (1 cabinet per carton)
Colour	Black
Options	Available on white and Ral colours on request
Rigging	Ohm cups and feet stacking system, stackable with TRS-218
HARDWARE	
Fitted as standard	Ohm cups and feet stacking system
Optional	EP-5 Connector Option
Additional Descriptive Data	Plywood construction, with durable scratch resistant, textured paint finish and kick-proof steel grill with stainless steel Ohm logo.

